



---

## ALITHICON MEGA-THERM SYNTHETIC HIGH TEMPERATURE BEARING LUBRICANT

THE ALITHICON MEGA-THERM SYNTHETIC HIGH TEMPERATURE BEARING LUBRICANT IS A NEW CONCEPT LUBRICANT, CONSISTING OF A FORMULATION OF NEVER-BEFORE USED INGREDIENTS, TO SUPPLY EXTRAORDINARY WEAR RESISTANCE IN TEMPERATURES RANGING FROM -40° F. TO 2,200° F. (-40° C. TO 1,204° C.).

THE ALITHICON MEGA-THERM LUBRICANT IS EASY TO APPLY, IN ITS GREASE OR PASTE FORM, AT AMBIENT TEMPERATURES, AND AFTER OPERATING TEMPERATURES HAVE EXCEEDED 800° F., THE FLUID LUBRICANT TOTALLY VOLATILIZES, LEAVING A NON-GUMMING OR NON-HARDENING RESIDUE WHICH CONTINUES TO PROVIDE PROTECTION IN EXTREME TEMPERATURES OF 2,200° F. THE ALITHICON MEGA-THERM LUBRICANT HAS AN AFFINITY TO METAL, WHICH ASSURES IT TO STAY PUT EVEN AT THE EXTREME ELEVATED TEMPERATURES.

THE ALITHICON MEGA-THERM LUBRICANT CONTAINS NO PARTICLES OF LEAD, COPPER, OR MOLYBDENUM DISULFIDE, SO IT IS SUITABLE FOR USE WITH STAINLESS ALLOYS, AT HIGH TEMPERATURES.

IT IS SOLUBLE WITH HYDROCARBON AND CHLOROHYDROCARBON SOLVENTS, AND INSOLUBLE WITH POLAR SOLVENTS, SUCH AS WATER, ETHYL ALCOHOL, ISO-PROPYL ALCOHOL, ACETONE, METHYL-ETHYL-KETONE AND GLACIAL ACETIC ACID, AT AMBIENT TEMPERATURES.

THE ALITHICON MEGA-THERM LUBRICANT IS EXCELLENT FOR USE IN HEAVY LOADED BEARINGS OR SLIDE APPLICATIONS. IT IS OUTSTANDING FOR JOURNAL AND CLOSE-TOLERANCE BEARINGS.

### USER BENEFITS:

- \* WATERPROOF \* CHEMICAL RESISTANT \* WILL NOT HARDEN IN SERVICE
- \* TIMKEN O.K. LOAD RATING, 120 lbs, MIN. \* GREATLY EXTENDS BEARING LIFE
- \* OPERATING TEMPERATURE RANGE -40° F. TO 2,200° F. (-40° C. TO 1,204° C.)
- \* ACCEPTABLE OPERATING BEARING SPEEDS 0 8,000 R.P.M.'S \* NON MELTING
- \* CONTAINS NO SILICONES

### APPLICATIONS:

SOAKING PIT COVERS, SOAKING PIT CRANES, ANNEALING PIT FURNACES, KILN CAR WHEELS, AGING OVEN CAR WHEEL BEARINGS, LADLE BEARINGS, OVEN CONVEYOR BEARINGS, HOMOGENIZER FAN BEARINGS, AGING OVEN FAN BEARINGS, AGING OVEN CAR WHEEL BEARINGS, EXPANDIBLE MANDRELS, EXTRUDER CASTING BEARINGS, AUTOCLAVES, SWEECO SCREEN BEARINGS, ROBBINS WEBB SCREEN BEARINGS, CALCINER BEARINGS, TEXTILE DRAW FRAME NEEDLE BEARINGS, ACUTATORS, ELECTRICAL GENERATING PLANTS, TURBINE GOVERNOR LINKAGE, TURBINE GIBS AND GUIDES, ECONOMIZER HOPPER BUTTERFLY VALVES, ALUMINUM PLANT PUSHER FURNACE INGOT CASTER RAILS, DAMPER BEARINGS, COATING DEPARTMENT PAPER ROLL SHEEVES BEARINGS, ROCK HAMMER PASTE LUBRICANT

THE ALITHICON MEGA-THERM SYNTHETIC HIGH TEMPERATURE BEARING LUBRICANT IS AVAILABLE IN (2) NLGI GRADES.

FOR TECHNICAL SPECIFICATIONS, SEE REVERSE SIDE

## ALITHICON MEGA-THERM SYNTHETIC HIGH TEMPERATURE BEARING LUBRICANT

TECHNICAL SPECIFICATION	ASTM TEST	MEGA-THERM 2	MEGA-THERM 5
NLGI GRADE		0	2
PENETRATION, WORKED 60 STROKES 100,000 STROKES	D-217	365 367	278 280
COLOR		SILVER	SILVER
DROPPING POINT	D-2265	NONE	NONE
BASE FLUID LUBRICANT VISCOSITY SUS @ 100° F.	D-445	745	745
FOUR-BALL WEAR TEST SCAR DIAMETER, mm, MAX.	D-2266	0.27	0.27
TIMKEN O.K. LOAD RATING, lbs, MIN.	2782	100	100
WATER WASH-OUT. 79° C. (175° F.), WT. %	D-1264	0.02	0.02
BASE FLUID VISCOSITY INDEX	D-2270	145	145
FOUR BALL E.P. TEST LOAD WEAR INDEX, kg. WELD LOAD, kg.	D-2783	160 800+	160 800+
FLUID LEAKAGE TENDENCIES, %	D-1263	0.4	0.2

### AVAILABLE PACKAGING: MEGA-THERM

\* 30 / 14.5 oz TUBE CASE \* 50 / 14.5 oz TUBE CASE  
\* 35 lb PAIL \* 120 lb KEG \* 420 lb DRUM

\* 3,000 lb TOTE / BULK

### MEGA-THERM COMPATIBLE LUBRICANTS

BARIUM COMPLEX	CALCIUM COMPLEX	ALUMINUM COMPLEX
CALCIUM STEARATE	BENTONE / CLAY	CALCIUM 12-HYDROXY
LITHIUM COMPLEX	POLYUREA	LITHIUM STEARATE
SILICA	SODIUM	LITHIUM 12-HYDROXY
CALCIUM SULFONATE COMPLEX		

ALITHICON LUBRICANTS CO., INC / P O BOX 5225 / ALBANY, GEORGIA 31706 PHONE: 229-883-9515 / FAX:  
229-883-9516 E-MAIL: ALITHICON@ALITHICON.COM / WEBSITE: [WWW.ALITHICON.COM](http://WWW.ALITHICON.COM)