



ALITHICON AL-32 PARA/SYNTHETIC **AIR CYLINDER LUBRICANT**

THE ALITHICON AL-32 PARA/SYNTHETIC AIR CYLINDER LUBRICANT IS A SPECIAL BLEND OF PREMIUM QUALITY PETROLEUM AND SYNTHETIC FLUIDS, FORMULATED TO ENTRAP THE MOISTURE WHICH IS NORMALLY FOUND IN AIR SUPPLY LINES AND PROVIDE SUPERIOR LUBRICATION TO AIR CYLINDERS AND AIR OPERATED TOOLS.

THE SLUDGE OR BUILD-UP NORMALLY FOUND IN AIR CYLINDERS AND AIR TOOLS, AFTER FAILURE, IS COMPLETELY ELIMINATED WHEN USING THE "ALITHICON AL-32". GALLING, SCUFFING, AND EXCESSIVE WEAR ARE GREATLY REDUCED, TOO.

THE USER OF THE "ALITHICON AL-32" PARA/SYNTHETIC AIR CYLINDER LUBRICANT CAN EXPECT 600% LONGER AIR CYLINDER AND AIR TOOL LIFE WHEN USED IN PLACE OF THE MORE COMMONLY USED OILS.

USER BENEFITS:

- * THE ELIMINATION OF SLUDGE OR BUILD-UP
- * EXCELLENT PROTECTION EVEN WHEN MOISTURE IS PRESENT
- * GREATLY REDUCES GALLING AND SCUFFING
- * GREATLY REDUCES AIR TOOL AND AIR CYLINDER WEAR
- * EXTENDS AIR TOOL AND AIR CYLINDER LIFE BY 600%

PACKAGING:

- | | |
|---------------------|------------------|
| * 24 / 1 QUART CASE | * 6 GALLON PAIL |
| * 6 / 1 GALLON CASE | * 55 GALLON DRUM |

SEE REVERSE SIDE FOR TYPICAL SPECIFICATIONS

ALITHICON "AL-32" PARA/SYNTHETIC AIR CYLINDER LUBRICANT

TYPICAL SPECIFICATIONS

ISO GRADE	32
SAE GRADE	10
VISCOSITY @ 40° C., c.S.t.	29.6
VISCOSITY @ 100° C., c.S.t.	5.2
VISCOSITY @ 100° F., c.S.t.	155.0
VISCOSITY @ 210° F., c.S.t.	44.4
VISCOSITY INDEX	125
FLASH POINT, ° F.	445
POUR POINT, ° F.	-5
GRAVITY, API	33.7
SPECIFIC GRAVITY @ 60° F.	0.87
POUNDS PER GALLON	7.11
COLOR	RED

ALITHICON LUBRICANTS CO., INC / P O BOX 5225 / ALBANY, GEORGIA 31706
PHONE: 229-883-9515 / FAX: 229-883-9516
E-MAIL: ALITHICON@ALITHICON.COM / WEBSITE: WWW.ALITHICON.COM