



ALITHICON FM-AL-26 SYNTHETIC FOOD MACHINERY AIR CYLINDER LUBRICANT

THE ALITHICON FM-AL-26 SYNTHETIC FOOD MACHINERY AIR CYLINDER LUBRICANT IS FORMULATED WITH USDA/FDA APPROVED SYNTHETIC FLUIDS AND FOOD GRADE ADDITIVES, MEETING WITH USDA/FDA APPROVED SYNTHETIC FLUIDS AND FOOD GRADE ADDITIVES, MEETING REQUIREMENTS FOR THE H-1 RATING UNDER TITLE 21 CFR. 178.3570, FOR USE IN FOOD AND POULTRY PLANTS WHERE INCIDENTAL CONTACT OF THE LUBRICANT WITH THE EDIBLE PRODUCTS BEING MANUFACTURED IS POSSIBLE.

THE ALITHICON FM-AL-26 SYNTHETIC FOOD MACHINERY AIR CYLINDER LUBRICANT IS ODORLESS, TASTELESS, AND COLORLESS, WATER CLEAR, YET IT WILL GREATLY EXTEND AIR TOOL LIFE, PLUS OPTIMIZE PNEUMATIC SYSTEM PERFORMANCE.

BECAUSE MOISTURE IS EVER-PRESENT IN AIR LINES, DUE TO THE EXPANSION AND COOLING OF COMPRESSED AIR, THE ALITHICON FM-AL-26 SYNTHETIC FOOD MACHINERY AIR CYLINDER LUBRICANT VIRTUALLY ELIMINATES TOOL VALVE STICKING, PREVENTS LUBRICATOR CLOGGING, AND INHIBITS POWER-THIEVING DEPOSITS BY ABSORBING SIGNIFIGANT AMOUNTS OF MOISTURE, WHICH CAUSES GUMMING. IN ADDITION, IT GREATLY EXTENDS THE LIFE OF INTERNAL PARTS BY REDUCING FRICTION AND WEAR.

WHEN USING THE ALITHICON FM-AL-26, GALLING, SCUFFING, AND GUMMING IN AIR CYLINDERS IS ELIMINATED.

USER BENEFITS:

- * EFFECTIVE AIR CYLINDER LUBRICANT MEETING USDA/FDA H-1 REQUIREMENTS
- * ELIMINATES AIR CYLINDER / AIR TOOL GALLING, SCUFFING, AND GUMMING
- * EXTENDS AIR CYLINDER / AIR TOOL LIFE AS MUCH AS 800%

PLEASE SEE REVERSE SIDE FOR TYPICAL SPECIFICATIONS

ALITHICON FM-AL-26 SYNTHETIC FOOD MACHINERY AIR CYLINDER LUBRICANT

TYPICAL SPECIFICATIONS	TEST RESULTS
VISCOSITY, CALCULATED SUS @ 100° F. SUS @ 210° F.	96 40
VISCOSITY, ASTM D-445 Cst. @ 40° C Cst. @ 100° c	26 4.9
VISCOSITY INDEX (ASTM D-2270)	121
LOAD CARRYING ABILITY FALEX TEST (ASTM D-2670) NON-SIEZURE LOAD, lbs.	1095
POUR POINT (ASTM D-97) ° F. ° C.	-5 -23
RUST TEST (ASTM D-665 A)	PASS

AVAILABLE PACKAGING:

- * 24 / 1 QUART CASE
- * 6 / 1 GALLON CASE
- * 6 GALLON PAIL
- * 55 GALLON DRUM
- * BULK