




MATERIAL SAFETY DATA SHEET

ALITHICON LUBRICANTS CO., INC.
P.O. BOX 5225 / ALBANY, GA 31706
www.alithicon.com / Alithicon@alithicon.com
Phone: (229) 883-9515 / Fax: (229) 883-9516



SECTION 1: IDENTIFICATION & EMERGENCY INFORMATION

PRODUCT: ALITHICON 822 SYNTHETIC HIGH TEMPERATURE CHAIN LUBRICANT

EMERGENCY PHONE: (229) 888-2520

CHEMICAL NAME: ADDITIVE COMPOUNDED SYNTHETIC FLUID

FORMULA: NOT APPLICABLE

SECTION II: INGREDIENTS

COMPONENTS	CAS NO	WT%	OSHA PEL	ACGIH TLV
HYDROGENATED POLYOLEFIN	68649-11-16	34.0	-----	-----
DI-ISODECYL ADIPATE	9003-29-6	64.0	-----	-----
ANTI-OXIDANT	128-37-0	2.0	-----	-----

*** **NOTE:** PRODUCT NOT CLASSIFIED AS HAZARDOUS UNDER OSHA 29CFR 1910.1200 AND IT DOES NOT CONTAIN ANY CHEMICALS THAT REQUIRE A WARNING UNDER CALIFORNIA PROPOSITION 65. SAFE OPERATING AND GOOD HOUSEKEEPING PRACTICES SHOULD ALWAYS BE FOLLOWED WHEN USING THIS PRODUCT. INHALATION OF FUMES AND MIST FROM FLUID SHOULD BE AVOIDED. ***

SECTION III: PHYSICAL & CHEMICAL DATA

SPECIFIC GRAVITY (H 0-1): .89 @ 16° C **BOILING PT:** 309° C **MELTING PT:** N/A
VAPOR PRESSURE (mm Hg): 0.01 **VAPOR DENSITY (AIR=1):** 12.0
EVAPORATION RATE (n-BUTYL ACETATE=1): < 0.0015
VOLUME % VOLATILE: NEGLIGIBLE **SOLUBILITY IN WATER:** NEGLIGIBLE
REACTIVITY WITH WATER: NONE
APPEARANCE & ODOR: CLEAR FLUID WITH A BLAND ODOR

SECTION IV: FIRE & EXPLOSION HAZARD DATA

FLASH POINT (METHOD): .329° C (CC)
FLAMMABLE LIMITS: **LEL=** 1% **UEL=** 6%
AUTO-IGNITION TEMPERATURE: 710° + F
EXTINGUISHING MEDIA: DRY CHEMICAL, CARBON DIOXIDE, WATER FOG, FOAM, INERT GAS
SPECIAL FIRE FIGHTING PROCEDURES: SELF CONTAINED BREATHING APPRATUS
UNUSUAL FIRE & EXPLOSION HAZARDS: AVOID STORAGE WITH OXIDIZING AGENTS.

SECTION V: REACTIVITY DATA

STABILITY: STABLE: (X) UNSTABLE ()
CONDITIONS TO AVOID: STRONG OXIDIZING MATERIALS
INCOMPATIBLE MATERIALS: STRONG ACIDS, ALKALINES AND OXIDIZERS SUCH AS CHLORENE AND OXYGEN
HAZARDOUS DECOMPOSITION PRODUCTS: N/A
HAZARDOUS POLYMERIZATION: (X) WILL NOT OCCUR () MAY OCCUR

SECTION VI: HEALTH HAZARD DATA

SYMPTOMS OF EXPOSURE: PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE SKIN IRRITATION. EYE CONTACT MAY CAUSE EYE IRRITATION. AVOID INHALATION OF OIL FUMES OR MIST FROM FLUID - MAY CAUSE RESPIRATORY IRRITATION. INGESTION MAY CAUSE ACUTE STOMACH DISTRESS AND LUNG DAMAGE IF LARGE QUANTITIES ARE SWALLOWED AND ASPIRATED.

EFFECTS OF OVEREXPOSURE: PROLONGED OR REPEATED SKIN CONTACT WITH THIS PRODUCT TENDS TO REMOVE SKIN OILS POSSIBLY LEADING TO IRRITATION AND DERMATITIS. HEALTH STUDIES HAVE SHOWN MANY PETROLEUM PRODUCTS POSE POTENTIAL RISKS WHICH VARY FROM PERSON TO PERSON. EXPOSURE TO LIQUID, VAPORS, OR MISTS SHOULD BE MINIMIZED.

IS MATERIAL LISTED AS CARCINOGEN OR POTENTIAL CARCINOGEN?: NO

NATIONAL TOXICOLOGY PROGRAM: NO **IRAC MONOGRAPHS:** NO **OSHA:** NO

EMERGENCY AND FIRST AID PROCEDURES (BY ROUTE OF ENTRY):

INHALATION: CLEAN AIR PASSAGE, CALL PHYSICIAN

INGESTION: IF INGESTED, CALL PHYSICIAN

EYES: WASH WITH COPIOUS QUANTITIES OF WATER

SKIN: REMOVE BY WIPING, OR WATERLESS HAND CLEANER, FOLLOWED BY WASHING

SECTION VII: SPILL OR LEAK PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: SCOOP UP EXCESS, WIPE UP WITH RAGS, PICK UP RESIDUE WITH DIATOMACEOUS EARTH TO AVOID WALKING HAZARD

WASTE DISPOSAL METHOD: INCINERATE ABSORBED MATERIAL. WASTE DISPOSAL METHODS MUST COMPLY WITH ALL APPLICABLE LOCAL, STATE, AND FEDERAL REGULATIONS.

*** NOTE: CONTAINS BARIUM AND ANTIMONY COMPOUNDS AT LESS THAN EPA "DE MINIMUS" REPORTING QUANTITY OF SECTION 313 RELEASE REPORTING REQUIREMENTS OF 40CFR372. NOT A RCRA OR CERCLA HAZARDOUS WASTE. ***

SECTION VIII: SPECIAL PROTECTION INFORMATION

RESPIRATORY PROTECTION (TYPE): N/R

VENTILATION: **LOCAL EXHAUST:** N/R **SPECIAL:** N/R **MECHANICAL:** N/R

OTHER: N/R

PROTECTION GLOVES: N/R **EYE PROTECTION:** N/R **OTHER:** N/R

OTHER PROTECTIVE EQUIPMENT: PERSONS WITH HYPERSENSITIVE SKIN SHOULD USE GLOVES

SPECIAL HYGIENIC PRACTICE: WASH HANDS BEFORE EATING

SECTION IX: SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN IN HANDLING & STORING: NORMAL PRECAUTIONS AS WITH A PETROLEUM PRODUCT

OTHER PRECAUTIONS: N/A

DATE REVISED: 03-26-06

PREPARED BY: DIAMOND JACK S. SMITH, SR.

DISCLAIMER

THE INFORMATION CONTAINED HEREIN IS ACCURATE AND RELIABLE AS OF THE DATE ISSUED TO THE BEST OF ALITHICON LUBRICANTS CO., INC.'S KNOWLEDGE. ALITHICON LUBRICANTS CO., INC. DOESN'T WARRANT OR GUARANTEE ITS ACCURACY OR RELIABILITY AND SHALL NOT BE LIABLE FOR ANY LOSS OR DAMAGE ARISING OUT OF THE USE THEREOF. IT IS THE USER'S RESPONSIBILITY TO SATISFY ITSELF THAT THE INFORMATION OFFERED FOR ITS CONSIDERATION IS SUITABLE FOR ITS PARTICULAR USE.